

SHENZHEN HEANSEN TECH CO., LTD

LINEAR ACTUATOR TECHNICAL SPECIFICATION

Customer Name:

Product Specification:HASZ08-2412-610/1000

NO	ITEM	SPECIFICATION	NOTE
1	Power source rated voltage/Frequency	/	
2	Switching power supply specified output	29V/2A	
3	Electrical machinery rated voltage	29VDC	
4	Electrical machinery rated current	2ADC	
5	Electrical machinery rated power	58W	
6	Idling current(Rise)	≤2.0A	
7	Idling current(drop)	≤2.0A	
8	Liad form	Push/Pull	
9	maximum thrust force	6000N	
10	maximum pilling force	4000N	
11	Protection rank	IP44	
12	Fixed working system	S2/18 2min ON 18min off	
13	Installment dimension of high position	610±2mm	
14	Installment dimension of low position	1000±2mm	
15	Stroke	390mm	
16	Idling traveling speed	4mm/s	
17	Vibration	Feel vibrated not obviously	
18	Noise	≤55Db(A)	Test distance: 300mm
19	Contour and installation size	Please see the outing drawing	
20	Appearance	Nobroken,contanina tion or corroiss	
		that would adversely effece either	
		the funtiong or the.unit	
21	Life span	>10000times	Duty cycle:10%

Date/Draft:

Date/Check:

Date/Approve: